

FORM PTO-1390
(REV 11-2000)

U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

ATTORNEY'S DOCKET NUMBER

TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371

MUR-8582US

U.S. APPLICATION NO. (if known, see 37 CFR 1.5)

10/019070

INTERNATIONAL APPLICATION NO.
PCT/GB00/02290INTERNATIONAL FILING DATE
23 June 2000PRIORITY DATE CLAIMED
23 June 1999

TITLE OF INVENTION

DYED FABRIC MATERIAL, METHOD OF PRODUCING THE SAME AND USE OF THE FABRIC
MATERIAL IN THE MANUFACTURE OF SPORTS BALLS

APPLICANT(S) FOR DO/EO/US

Alan John Brašier and David Anthony Smith

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☐ This is an express request to begin national examination procedures (35 U.S.C. 371(f)). The submission must include items (5), (6), (9) and (21) indicated below.
4. ☒ The US has been elected by the expiration of 19 months from the priority date (Article 31).
5. ☐ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
 - a. ☐ is attached hereto (required only if not communicated by the International Bureau).
 - b. ☐ has been communicated by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☐ An English language translation of the International Application as filed (35 U.S.C. 371(c)(2)).
 - a. ☐ is attached hereto.
 - b. ☐ has been previously submitted under 35 U.S.C. 154(d)(4).
7. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
 - a. ☐ are attached hereto (required only if not communicated by the International Bureau).
 - b. ☐ have been communicated by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☒ have not been made and will not be made.
8. ☐ An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☒ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. ☒ A copy of the International Preliminary Examination Report (PCT/IPEA/409) with annexed amended claims.

Items 11 to 20 below concern documents(s) or information included:

11. ☒ An Information Disclosure Statement under 37 U.S.C. 1.97 and 1.98.
12. ☒ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☒ A FIRST preliminary amendment.
14. ☐ A SECOND or SUBSEQUENT preliminary amendment.
15. ☐ A substitute specification.
16. ☐ A change of power of attorney and/or address letter.
17. ☐ A computer readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C. 1.821 - 1.825.
18. ☒ A second copy of the published international application under 35 U.S.C. 154(d)(4).
19. ☐ A second copy of the English language translation of the international application under 35 U.S.C. 154(d)(4).
20. ☐ Other items or information:

10019070.132001

Form PTO-1390 (Rev. 10-2001) page 2 of 2

MUR-8582US

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Alan John Brasier and David : Interntl Appli. No.:
Anthony Smith PCT/GB00/02290
Serial No.: (to be assigned) : Interntl Filing Date:
Filed: (herewith) : 23 June 2000
FOR: DYED FABRIC MATERIAL, :
METHOD OF PRODUCING
THE SAME AND USE OF
THE FABRIC MATERIAL IN
THE MANUFACTURE OF
SPORTS BALLS

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents
Washington, D.C. 20231

S I R :

Preliminary to examination in the United States Patent and
Trademark Office, please make the following amendments in the above-
identified application in order to place it in condition for examination.

IN THE SPECIFICATION:

Amend the specification by inserting before the first line the
sentence:

This application is the U.S. national phase application of PCT
International Application No. PCT/GB00/02290 filed 23 June 2000.

1AMUR\8582US\PREAMEND

10019070.122001

IN THE CLAIMS:

Please replace claims 3-5, 8-15, 17, 20-24, 29-31, 34-38, 41-46 and 48 with the following amended claims:

1 3. (Amended) The method as claimed in Claim 1, wherein
2 said yellow dye has a colour index number acid yellow 250.

1 4. (Amended) The method as claimed in Claim 1, wherein
2 said material is made from a mixture of fibres of different types.

1 5. (Amended) The method as claimed in Claim 1, wherein
2 said material comprises a mixture of wool and synthetic fibres.

1 8. (Amended) The method as claimed in Claim 1, wherein the
2 content of wool fibres in said material is at least 20% by weight.

1 9. (Amended) The method as claimed in Claim 1, wherein the
2 content of wool fibres in said material is at least 25% by weight.

1 10. (Amended) The method as claimed in Claim 1, wherein the
2 content of wool fibres in said material is at least 40% by weight.

1 11. (Amended) The method as claimed in Claim 1, wherein
2 said weft yarns comprise at least 20% by weight of wool.

1 12. (Amended) The method as claimed in Claim 1, wherein
2 said weft yarns comprise at least 30% by weight of wool.

10019070.122001

1 13. (Amended) The method as claimed in Claim 1, wherein
2 said weft yarns comprise at least 40% by weight of wool.

1 14. (Amended) The method as claimed in Claim 1, wherein
2 said material is processed in piece form.

1 15. (Amended) The method as claimed in Claim 1, wherein
2 said material is contacted with a partitioning agent.

1 17. (Amended) The method as claimed in Claim 1, wherein
2 said material is treated using a jet-dyeing apparatus.

1 20. (Amended) The method as claimed in Claim 1, wherein
2 said material is contacted with the bleaching agent prior to said material being
3 contacted with said fluorescent dye.

1 21. (Amended) The method as claimed in Claim 15, wherein
2 said material is contacted with the partitioning agent prior to said material being
3 contacted with said fluorescent dye.

1 22. (Amended) The method as claimed in Claim 15, wherein
2 said bleaching agent is added simultaneously or quasi-simultaneously with the
3 partitioning agent.

1 23. (Amended) The method as claimed in Claim 1, wherein
2 said bleaching agent is an inorganic reducing agent with chelating agents and
3 comprises 30-40% by weight tetrasodium ethylene-diaminetetraacetate and 30-
4 40% by weight disodium disulphite.

10019070.122001

1 24. (Amended) A coloured fabric material obtainable according
2 to the method described in Claim 1.

1 29. (Amended) The fabric material as claimed in Claim 27,
2 wherein said lightness value is 96 or more.

1 30. (Amended) The fabric material as claimed in Claim 27,
2 wherein said reflectance value is 125 or more.

1 31. (Amended) The fabric material as claimed in Claim 27,
2 which exhibits the following characteristics:

3 i) a chroma value of 110 or more;

4 ii) a lightness value of 97 or more; and

5 iii) a reflectance value of 128 or more.

1 34. (Amended) A white fabric material as claimed in Claim 32,
2 having a lightness value of 92 or greater.

1 35. (Amended) A white fabric material as claimed in Claim 32,
2 having a reflectance value of 85 or more.

1 36. (Amended) A white fabric material as claimed in Claim 32,
2 which exhibits the following characteristics:

3 i) a chroma value of 5 or less;

4 ii) a lightness value of 93 or more; and

10019070-122001

5 iii) a reflectance value of 90 or more.

1 37. (Amended) A fabric material as claimed in Claim 27,
2 wherein said material is made of a mixture of fibres of different types.

1 38. (Amended) A fabric material as claimed in Claim 27,
2 wherein said material comprises a mixture of wool and synthetic fibres.

1 41. (Amended) A fabric material as claimed in Claim 27,
2 wherein the content of wool fibres in said material is at least 20% by weight.

1 42. (Amended) A fabric material as claimed in Claim 27,
2 wherein the content of wool fibres in said material is at least 40% by weight.

1 43. (Amended) A fabric material as claimed in Claim 27,
2 wherein said weft yarns comprise at least 20% by weight of wool.

1 44. (Amended) A fabric material as claimed in Claim 27,
2 wherein said weft yarns comprise at least 30% by weight of wool.

1 45. (Amended) A fabric material as claimed in Claim 27,
2 wherein said weft yarns comprise at least 40% by weight of wool.

1 46. (Amended) A sports ball having a fabric material outer
2 surface, said fabric material being a fabric material as defined in Claim 27.

1 48. (Amended) A sports ball having a fabric material outer
2 surface, said fabric material being a fabric material as obtained by the method of
3 Claim 1.

10019070.122001

IN THE ABSTRACT:

Please include an Abstract on a separate sheet as enclosed
herewith.

Respectfully submitted,



Allan Ratner, Reg. No. 19,717
Attorney for Applicant

AR/lk


Dated: December 20, 2001

P.O. Box 980
Valley Forge, PA 19482
(610) 407-0700

The Assistant Commissioner for Patents is
hereby authorized to charge payment to
Deposit Account No. 18-0350 of any fees
associated with this communication.

EXPRESS MAIL Mailing Label Number: EL 923264464 US
Date of Deposit: December 20, 2001

I hereby certify that this paper and fee are being deposited, under 37 C.F.R. § 1.10 and with sufficient postage, using the "Express Mail Post Office to Addressee" service of the United States Postal Service on the date indicated above and that the deposit is addressed to the Assistant Commissioner for Patents, U.S. Patent & Trademark Office, Washington, D.C. 20231, Attn: BOX PCT/EO/US.



Kathleen Libby

10019070.122001

ABSTRACT

A method of dyeing fabric material which comprises the step of contacting said fabric material with a bleaching agent prior to or simultaneously with contacting said fabric material with a dyestuff providing said colour. The fabric material so obtained is suitable for use in sports ball manufacture, especially tennis ball manufacture. The coloured fabric material preferably includes wool fibres and exhibits the following characteristics after dyeing: i) a chroma value of 100 or more; ii) a lightness value of 95 or more; and iii) a reflectance value of 120 or more. Preferably the dye is a yellow fluorescent dye.

10019070-122001

VERSION WITH MARKINGS TO SHOW CHANGES MADE

IN THE SPECIFICATION:

Specification at page 1, line 1:

- 1 This application is the U.S. national phase application of PCT
2 International Application No. PCT/GB00/02290 filed 23 June 2000.

IN THE CLAIMS:

- 1 3. (Amended) The method as claimed in ~~either Claim 1 or 2~~
2 Claim 1, wherein said yellow dye has a colour index number acid yellow 250.
- 1 4. (Amended) The method as claimed in ~~any one of Claims 1~~
2 ~~to 3~~ Claim 1, wherein said material is made from a mixture of fibres of different
3 types.
- 1 5. (Amended) The method as claimed in ~~any one of Claims 1~~
2 ~~to 4~~ Claim 1, wherein said material comprises a mixture of wool and synthetic
3 fibres.
- 1 8. (Amended) The method as claimed in ~~any one of Claims 1~~
2 ~~to 7~~ Claim 1, wherein the content of wool fibres in said material is at least 20%
3 by weight.

10019070-122001

1 9. (Amended) The method as claimed in ~~any one of Claims 1~~
2 ~~to 8~~ Claim 1, wherein the content of wool fibres in said material is at least 25%
3 by weight.

1 10. (Amended) The method as claimed in ~~any one of Claims 1~~
2 ~~to 9~~ Claim 1, wherein the content of wool fibres in said material is at least 40%
3 by weight.

1 11. (Amended) The method as claimed in ~~any one of Claims 1~~
2 ~~to 10~~ Claim 1, wherein said weft yarns comprise at least 20% by weight of
3 wool.

1 12. (Amended) The method as claimed in ~~any one of Claims 1~~
2 ~~to 10~~ Claim 1, wherein said weft yarns comprise at least 30% by weight of
3 wool.

1 13. (Amended) The method as claimed in ~~any one of Claims 1~~
2 ~~to 10~~ Claim 1, wherein said weft yarns comprise at least 40% by weight of
3 wool.

1 14. (Amended) The method as claimed in ~~any one of Claims 1~~
2 ~~to 13~~ Claim 1, wherein said material is processed in piece form.

1 15. (Amended) The method as claimed in ~~any one of Claims 1~~
2 ~~to 14~~ Claim 1, wherein said material is contacted with a partitioning agent.

1 17. (Amended) The method as claimed in ~~any one of Claims 1~~
2 ~~to 16~~ Claim 1, wherein said material is treated using a jet-dyeing apparatus.

10019070.122001

1 20. (Amended) The method as claimed in ~~any one of Claims 1~~
2 ~~to 19~~ Claim 1, wherein said material is contacted with the bleaching agent prior
3 to said material being contacted with said fluorescent dye.

1 21. (Amended) The method as claimed in ~~any one of Claims 15~~
2 ~~to 16~~ Claim 15, wherein said material is contacted with the partitioning agent
3 prior to said material being contacted with said fluorescent dye.

1 22. (Amended) The method as claimed in ~~any one of Claims~~
2 ~~15, 16 and 18~~ Claim 15, wherein said bleaching agent is added simultaneously or
3 quasi-simultaneously with the partitioning agent.

1 23. (Amended) The method as claimed in ~~any one of Claims 1~~
2 ~~to 22~~ Claim 1, wherein said bleaching agent is an inorganic reducing agent with
3 chelating agents and comprises 30-40% by weight tetrasodium ethylene-
4 diaminetetraacetate and 30-40% by weight disodium disulphite.

1 24. (Amended) A coloured fabric material obtainable according
2 to the method described in ~~any one of Claims 1 to 23~~ Claim 1.

1 29. (Amended) The fabric material as claimed in ~~either one of~~
2 ~~Claims 27 and 28~~ Claim 27, wherein said lightness value is 96 or more.

1 30. (Amended) The fabric material as claimed in ~~any one of~~
2 ~~Claims 27 to 29~~ Claim 27, wherein said reflectance value is 125 or more.

1 31. (Amended) The fabric material as claimed in ~~any one of~~
2 ~~Claims 27 to 29~~ Claim 27, which exhibits the following characteristics:

10019070.122001

- 3 i) a chroma value of 110 or more;
- 4 ii) a lightness value of 97 or more; and
- 5 iii) a reflectance value of 128 or more.

1 34. (Amended) A white fabric material as claimed in ~~either one~~
2 ~~of Claims 32 and 33~~ Claim 32, having a lightness value of 92 or greater.

1 35. (Amended) A white fabric material as claimed in ~~any one of~~
2 ~~Claims 32 to 34~~ Claim 32, having a reflectance value of 85 or more.

1 36. (Amended) A white fabric material as claimed in ~~any one of~~
2 ~~claims 32 to 35~~ Claim 32, which exhibits the following characteristics:

- 3 i) a chroma value of 5 or less;
- 4 ii) a lightness value of 93 or more; and
- 5 iii) a reflectance value of 90 or more.

1 37. (Amended) A fabric material as claimed in ~~any one of~~
2 ~~Claims 27 to 36~~ Claim 27, wherein said material is made of a mixture of fibres
3 of different types.

1 38. (Amended) A fabric material as claimed in ~~any one of~~
2 ~~Claims 27 to 37~~ Claim 27, wherein said material comprises a mixture of wool
3 and synthetic fibres.

10019070.122001

1 41. (Amended) A fabric material as claimed in ~~any one of~~
2 ~~Claims 27 to 44~~ Claim 27, wherein the content of wool fibres in said material is
3 at least 20% by weight.

1 42. (Amended) A fabric material as claimed in ~~any one of~~
2 ~~Claims 27 to 44~~ Claim 27, wherein the content of wool fibres in said material is
3 at least 40% by weight.

1 43. (Amended) A fabric material as claimed in ~~any one of~~
2 ~~Claims 27 to 42~~ Claim 27, wherein said weft yarns comprise at least 20% by
3 weight of wool.

1 44. (Amended) A fabric material as claimed in ~~any one of~~
2 ~~Claims 27 to 43~~ Claim 27, wherein said weft yarns comprise at least 30% by
3 weight of wool.

1 45. (Amended) A fabric material as claimed in ~~any one of~~
2 ~~Claims 27 to 44~~ Claim 27, wherein said weft yarns comprise at least 40% by
3 weight of wool.

1 46. (Amended) A sports ball having a fabric material outer
2 surface, said fabric material being a fabric material as defined in ~~any one of~~
3 ~~Claims 27 to 45~~ Claim 27.

1 48. (Amended) A sports ball having a fabric material outer
2 surface, said fabric material being a fabric material as obtained by the method of
3 ~~any one of Claims 1 to 24~~ Claim 1.

10019070.122001

1 DYED FABRIC MATERIAL, METHOD OF PRODUCING THE SAME
2 AND USE OF THE FABRIC MATERIAL IN THE MANUFACTURE OF
3 SPORTS BALLS
4

5 The present invention relates to fabric material
6 particularly suitable for the manufacture of sports
7 balls and to a method of obtaining the same. More
8 particularly it relates to a new method of dyeing
9 woven or not woven material which provides the
10 material with high visibility characteristics. The
11 invention also relates to the dyed material thus
12 obtained and to the use of such material for the
13 manufacture of sports products and particularly for
14 the covering of tennis balls.
15

16 Traditionally, tennis balls were covered with white
17 woollen felt. Several decades ago yellow felt was
18 introduced for use on match quality balls and from
19 the early 1970's balls covered with yellow felt
20 became increasingly popular. Today, the vast

1 majority of tennis balls are covered with yellow
2 felt. Rule 3 of the International Tennis Federation
3 Rules of Tennis states "The ball shall have a uniform
4 outer surface consisting of a fabric cover and shall
5 be white or yellow in colour...".
6

7 The felt used on tennis balls was previously made
8 from wool. Increased wear properties are obtained by
9 including a proportion of synthetic fibres in the
10 felt, and nowadays such felt is usually made of a
11 mixture of wool and nylon fibres. The proportions of
12 wool and synthetic fibres used to produce the felt
13 can vary, but typically a ratio of 40:60 to 60:40 can
14 be used (by weight of weft yarn). It is desirable
15 that the side of the felt termed the "back" (which is
16 the side which will be stuck to the ball) is made of
17 a material which provides good adhesion when it is
18 glued on the internal rubber sphere of the ball.
19 Usually the backing is formed by using 100% cotton
20 warp yarns, but alternatives such as polyester and
21 nylon could be used.
22

23 The tennis ball felt is then preferably dyed with a
24 fluorescent dyestuff. That is, the coloured felt
25 will absorb ultra-violet light and re-emit the
26 absorbed energy in the visible area of the spectrum.
27 Most tennis balls are now covered with felt that is
28 dyed fluorescent yellow and which produces peak
29 reflectance values of over 100% in the yellow area of
30 the spectrum.
31

10019070 122001

1 Few manufacturers produce fluorescent dyestuffs
2 suitable for both wool and polyamide fibres. To the
3 best of the Applicant's knowledge all the major
4 tennis ball felt manufacturers use the same class of
5 dyestuff albeit from different dyestuff suppliers.
6 This class of dyestuff gives a hue (colour) slightly
7 to the green side of yellow.

8
9 The cones in the human eye are mainly responsible for
10 daylight colour vision and these give the eye the
11 highest visual efficiency in the yellow wavelengths.
12 In addition to percentage reflectance three other
13 values can be plotted to identify a colour:

14
15 Lightness, with a scale of 0 to 100, 0 being black
16 and 100 white;

17
18 Hue, which can be shown as a circle with red at 0
19 degrees and yellow, green and blue at 90 degree
20 intervals from this, the exact angle therefore
21 indicating the hue. If the lightness is visualised
22 as a vertical axis passing through the centre of the
23 hue circle, then a colour can be plotted in three
24 dimensional space; and

25
26 Chroma or colour saturation which can be shown as the
27 distance along a given radius from the centre of the
28 hue circle.

29
30 In the mid 1990's a high visibility yellow felt (or
31 Hi.Viz. F/Y) was produced using an increased

1001070.122001

1 percentage of dyestuff. This felt (or Hi.Viz. F/Y)
2 has a higher level of saturation (chroma) but
3 actually has a slight reduction in peak reflectance
4 and in lightness when compared to some standard
5 coloured felt.

6
7 A method has now been found which allows the
8 production of coloured felt for tennis balls having
9 enhanced visibility properties over the prior art.

10
11 The invention also provides a method of dyeing
12 material which produces an Ultra High Visibility
13 (UHV) felt which mitigates shortfalls of previously
14 available dyed felts.

15
16 More particularly, the invention provides a method of
17 dyeing fabric material (particularly fabric material
18 which is suitable for use in sports ball manufacture)
19 which method comprises contacting said fabric
20 material with a bleaching agent prior to or
21 simultaneously with contacting said fabric material
22 with a dyestuff providing said colour. The term
23 "fabric material" includes both piece goods, yarns
24 and also fibres in loose form.

25
26 The present invention is based on the fact that the
27 felt used to produce tennis balls typically has a
28 significant wool content (usually 40% or higher).
29 However, the peak reflectance of natural wool fibre
30 in the yellow area of the spectrum is typically
31 around 75% due to the natural yellowish-tinge in even

10019070.122001

1 the whitest wool. By means of comparison, titanium
2 dioxide treated nylon would typically have a 90%
3 reflectance. We have found that the naturally low
4 reflectance of wool limits the reflectance achievable
5 even with a fluorescent dye.

6
7 The need to bleach a yellowish-fibre (natural wool)
8 prior to or during dyeing that fibre yellow appears
9 counter-intuitive, but we have found that the
10 performance of the dye applied is greatly enhanced by
11 this step.

12
13 Preferably the material to be dyed is a felt and
14 especially a woven felt.

15
16 Preferably the material to be dyed comprises a
17 mixture of fibres of different types, for example, a
18 mixture of wool and synthetic (e.g. polyamide or
19 polyester) fibres. Preferred synthetic fibres are
20 polyamide fibres, for example Nylon 6,6 or Nylon 6.
21 We have found Nylon 6,6 to be most suitable. One or
22 more different synthetic fibres may be present in the
23 fabrics material.

24
25 The proportions of wool and synthetic fibres may vary
26 according to the consumer's requirements on cost and
27 performance of the fabric material. For woven
28 fabrics having warp and weft yarns, a wool content of
29 at least 20% (usually 25%) by weight of weft yarn is
30 required.

31

10039070.122001

1 We have found that better quality fabric material is
2 achieved with increased wool content - for example
3 30% or higher by weight of weft yarn. Typically a
4 wool content of 40% or above, for example 50% or 60%,
5 by weight of weft yarn achieves good results. It may
6 be desirable to use fabric having a wool content of
7 over 45% by weight of weft yarn and in certain high
8 quality fabric materials, like those used for high
9 quality tennis balls, over 50% (usually around 60%)
10 is used. In some cases the wool content may be even
11 higher (e.g. over 65% or 70% by weight of weft yarn)
12 and be 80% or over.

13
14 For woven fabric, the warp yarn will typically be a
15 cotton yarn, but polyester or polyamide (e.g. nylon)
16 could alternatively be used. For non-woven fabrics
17 (e.g. needlefelted fabrics) or knitted fabrics a
18 lower wool content (for example in the range of 20-
19 40% by weight, preferably at least 25%) may be
20 sufficient. By "wool" we include wool-like fibres
21 (e.g. angora, cashmere and mohair) as well as the
22 more typical sheep's wool.

23
24 Nylon fibres having a circular cross-section have
25 been successfully used, but synthetic fibres having
26 other cross-sections (e.g. triangular or flattened)
27 are commercially available and may further increase
28 the reflectance achievable.

29
30 It is also preferred that the material is processed
31 as described in piece form. Preferably the fabric is

10019070.122001

1 a felt and more particularly a felt suitable for the
2 covering of tennis balls. Since a mixture of fibre
3 types (wool and synthetic) are present in the fabric
4 material, it is recommended to contact the fabric
5 material also with a partitioning agent in order to
6 eliminate or reduce the difference in uptake of the
7 dyestuff between the different types of fibres. The
8 bleaching agent, which is preferably a reduction
9 bleaching agent, whitens the initial colour of at
10 least the wool.

11
12 Preferably the fabric material is treated using a
13 jet-dyeing apparatus and a liquor ratio of 6:1 to 8:1
14 is used to run the machine.

15
16 It is further preferred that the pH is adjusted
17 preferably between 4.2 and 4.5 by using, for example,
18 formic acid. The temperature is then raised to a
19 suitable temperature, for example about 45°C, and
20 held for a period of, typically, 3 minutes to be able
21 to check and if necessary adjust the pH.

22
23 A wide range of suitable partitioning agents are
24 available depending for example upon the nature of
25 the material to be treated. However the partitioning
26 agent sold under the Trade Name BASOPAL NA by BASF
27 plc of Cheshire, SK8 6QG, United Kingdom, has
28 demonstrated good results. BASOPAL NA is an
29 alkylarylsulphonate in water and comprises 50-60% by
30 weight of the salt of dodecylbenzenesulphonic and
31 triethanolamine. The concentration of BASOPAL NA

100221 02061001

1 recommended is about 0.5 grams per litre of liquor.
2 Alternative partitioning agents include THIOTAN RMFN
3 LIQUID (an anionic sulphated fatty acid, pH 7 to 8 at
4 10% dilution) to be used at a concentration of 3.0 to
5 0.1% (o.w.f.); and ERIONAL RF of Ciba Speciality
6 Chemicals Inc, Basel, Switzerland (an anionic
7 condensation product of aromatic sulphonic acids and
8 formaldehyde, pH 3.5 at 5% solution) to be used at a
9 concentration of 0.5 to 6% gram per litre liquor.

10

11 It is further preferred that the bleaching agent and,
12 if appropriate, the partitioning agent be in contact
13 with the material for a reasonable length of time
14 (typically from 1 to 30 mins) prior to the dyeing
15 step being executed.

16

17 It is further preferred that the bleaching agent be
18 added simultaneously or quasi-simultaneously with the
19 partitioning agent.

20

21 The bleaching agent preferably used is the one sold
22 under the Trade Name LUFIBROL FW by BASF plc of
23 Cheshire, SK8 6QG, United Kingdom. LUFIBROL FW is an
24 inorganic reducing agent with chelating agents and
25 comprises 30-40% by weight tetrasodium ethylene-
26 diaminetetraacetate and 30-40% by weight disodium
27 disulphite. The amount of LUBRIFOL FW used is
28 advantageously about 2% of the weight of fibre.
29 Alternative bleaching agents include LANALBIN BE
30 powder (a non-ionic hydroxylamine derivative, pH 5.6-
31 5.7 at 1 g/litre) to be used at a concentration of

10015070.122001

1 1.0 to 4.0% (o.w.f.); and ERIOCLARITE B of Ciba
2 Speciality Chemicals Inc of Basle, Switzerland (an
3 anionic mixture of sodium metabisulphite with the
4 sodium salt of ethylenediamine tetraacetic acid, pH 6
5 at 5% solution) to be used at a concentration of 0.5
6 to 1 g/litre.

7
8 It is preferred to use a fluorescent dye.

9 It is further preferred to use a yellow dye, as this
10 colour is highly desirable for the manufacture of
11 tennis balls. The preferred yellow dye which can be
12 used according to the invention is a dye having a
13 colour index number acid yellow 250, for example the
14 one sold under the Trade Name NYLOMINE FLAVINE C-7G
15 dyestuff by BASF plc, of Cheshire, SK8 6QG, United
16 Kingdom. The dyeing step can be performed according
17 to the recommended practice. A typical method is to
18 add the dyestuff to the material and the liquor
19 according to a recommended concentration and the
20 temperature is then raised to the recommended level
21 and held for some time at this temperature before
22 rinsing.

23
24 The method of the invention also provides a white
25 fabric material having enhanced visibility
26 properties. The method is similar to that described
27 above except that the "dyestuff" referred to is an
28 optical brightening agent. Optical brightening
29 agents are commonly used in the dyeing industry. The
30 brightening agent sold under the trade name UVITEX

10019070.122001

1 NFB by Ciba Speciality Chemicals Inc of Basle,
2 Switzerland can advantageously be used.

3
4 The invention also relates to the dyed material,
5 preferably a felt, and more preferably a woven felt,
6 obtained according to the method of the invention
7 which is coloured, preferably in yellow, and displays
8 enhanced visibility properties.

9
10 The invention further relates to the use of coloured
11 fabric material dyed according to the method of the
12 invention in the manufacture of articles such as
13 sporting articles and more particularly tennis balls.

14
15 The invention further relates to sporting articles
16 comprising the dyed fabric material, and more
17 particularly to sports balls (in particular tennis
18 balls) covered with such material.

19
20 The present invention provides a fabric material
21 suitable for use in sports ball manufacture, wherein
22 said material includes wool fibres and exhibits the
23 following characteristics:

24
25 a) for a coloured (non-white) fabric material:

- 26
27 i) a chroma value of 100 or more;
28 ii) a lightness value of 95 or more; and
29 iii) a reflectance value of 120 or more, or

30
31 b) for a white fabric material:

- 1 i) a chroma value of 14 or less;
- 2 ii) a lightness value of 85 or more; and
- 3 iii) a reflectance value of 100 or more.

4

5 When the dyed material is a woven fabric having warp
6 and weft yarns, a wool content of at least 20%
7 (usually 25%) by weight of weft yarn is required.

8 Desirably, the wool content includes at least 30% or
9 more, preferably 40% or more, by weight of weft yarn.

10 It may be desirable to use fabric having a wool
11 content of over 45% by weight of weft yarn and in
12 certain high quality fabric materials, like those
13 used for high quality tennis balls, over 50% (usually
14 around 60%) is used. In some cases the wool content
15 may be even higher (e.g. 65% or 70% by weight of weft
16 yarn) and be 80% or over.

17

18 For non-woven fabric the minimum amount of wool
19 required is about 20% by weight. Desirably, the wool
20 content includes at least 30% or more, preferably 40%
21 or more, by weight. It may be desirable to use over
22 45% by weight of wool and in certain high quality
23 fabric materials 50% by weight of wool, or even 60%
24 by weight of wool (e.g. 65% by weight of wool or even
25 up to 70% by weight of wool) may be employed.

26

27 For a coloured (non-white) fabric material the chroma
28 value may be higher than 100 (for example 102 or
29 more, preferably 105 or more) and, generally, a high
30 chroma value is desirable provided that the minimum
31 lightness and reflectance values given above for a

10019070-122001

1 coloured (non-white) fabric material are maintained.
2 We have achieved a chroma value of over 110,
3 specifically a value of 113.4.

4
5 Likewise, for a coloured (non-white) fabric material
6 a lightness value of greater than 95 is desirable
7 (for example of 96 or more, or even 97 or more)
8 provided that the minimum chroma and reflectance
9 values given above for a coloured (non-white) fabric
10 material are also maintained.

11
12 Similarly, for a coloured (non-white) fabric material
13 a reflectance value of over 120 (for example 125 or
14 more, preferably 128 or more) is desirable provided
15 that the minimum lightness and chroma values given
16 above for a coloured (non-white) fabric material are
17 also maintained. We have achieved a reflectance
18 value of over 129, specifically a value of 129.9.

19
20 In a preferred embodiment, the coloured (non-white)
21 fabric material according to the present invention
22 exhibits the following characteristics:

- 23 i) a chroma value of 105 or more
24 (preferably 110 or more);
25 ii) a lightness value of 96 or more
26 (preferably 97 or more); and
27 iii) a reflectance value of 125 or more
28 (preferably 128 or more).

29
30 Preferably the coloured (non-white) fabric material
31 is a yellow material.

1 For a white fabric material, the chroma value is
2 desirably lower than 10 (for example is 8 or less,
3 preferably is 5 or less) and, generally, a low chroma
4 value (indicating absence of colour) is desirable
5 provided that the minimum lightness and reflectance
6 values given above for a white fabric material are
7 maintained.

8
9 Likewise, for a white fabric material a lightness
10 value of greater than 85 is desirable (for example of
11 88 or more, 89 or more, or 90 or more) provided that
12 the maximum chroma value and minimum reflectance
13 value given above for a white fabric material are
14 maintained.

15
16 Similarly, for a white fabric material, a reflectance
17 value of over 100 (for example 102 or more, 105 or
18 more or 106 or more) is desirable provided that the
19 maximum chroma value and minimum reflectance value
20 given above for a white fabric material are
21 maintained.

22
23 In a preferred embodiment, the white fabric material
24 according to the present invention exhibits the
25 following characteristics:

- 26
27 i) a chroma value of 8 or less
28 (preferably 5 or less);
29 ii) a lightness value of 92 or more
30 (preferably 93 or more); and

- 1 iii) a reflectance value of 85 or more
2 (preferably 90 or more).
3

4 The present invention further provides a sports ball
5 having a fabric material surface (for example a
6 tennis ball) wherein said sports ball is manufactured
7 using a fabric material as defined above.
8

9 In a further aspect, the present invention provides a
10 sports ball having a fabric material outer surface
11 (for example a tennis ball) wherein said fabric
12 material forming said outer surface includes wool
13 fibres and exhibits the chroma, lightness and
14 reflectance value described above.
15

16 In a further aspect, the present invention provides a
17 sports ball having a white fabric material outer
18 surface (for example a tennis ball) wherein said
19 fabric material forming said outer surface includes
20 wool fibres and exhibits the following
21 characteristics :
22

- 23 i) a chroma value of 10 or less;
24 ii) a lightness value of 90 or more; and
25 iii) a reflectance value of 80 or more.
26

27 When the dyed material is a woven fabric having warp
28 and weft yarns, a wool content of at least 20%
29 (usually 25%) by weight of weft yarn is required.
30 Desirably, the wool content is at least 30% or more,
31 preferably 40% or more, by weight of weft yarn. It

10039070-122001

1 may be desirable to use fabric having a wool content
2 of over 45% by weight of weft yarn and in certain
3 high quality fabric materials, like those used for
4 high quality tennis balls, over 50% (usually around
5 60%) is used. In some cases the wool content may be
6 even higher (e.g. over 65% or 70% by weight of weft
7 yarn) and be 80% or over.

8
9 For non-woven fabric the minimum amount of wool
10 required is about 20% by weight. Desirably, the wool
11 content includes at least 30% or more, preferably 40%
12 or more, by weight. It may be desirable to use over
13 45% by weight of wool and in certain high quality
14 fabric materials 50% by weight of wool, or even 60%
15 by weight of wool (e.g. 65% by weight of wool or even
16 up to 70% by weight of wool) may be employed.

17
18 For a white fabric material, the chroma value is
19 desirably lower than 10 (for example is 8 or less,
20 preferably is 5 or less) and, generally, a low chroma
21 value (indicating absence of colour) is desirable
22 provided that the minimum lightness and reflectance
23 values given above for a white fabric material are
24 maintained.

25
26 Likewise, for a white fabric material a lightness
27 value of greater than 90 is desirable (for example of
28 92 or more, 93 or more, or 94 or more) provided that
29 the maximum chroma value and minimum reflectance
30 value given above for a white fabric material are
31 maintained.

10019070.122001

1 Similarly, for a white fabric material, a reflectance
2 value of over 80 (for example 85 or more, 90 or more
3 or 95 or more) is desirable provided that the maximum
4 chroma value and minimum reflectance value given
5 above for a white fabric material are maintained.

6

7 In a preferred embodiment, the white fabric material
8 according to the present invention exhibits the
9 following characteristics:

10

- 11 i) a chroma value of 8 or less
12 (preferably 5 or less);
13 ii) a lightness value of 92 or more
14 (preferably 93 or more); and
15 iii) a reflectance value of 85 or more
16 (preferably 90 or more).

17

18 The invention as described above with reference to
19 coloured (non-white) fabric material (both in respect
20 of the fabric material per se and in respect of the
21 sports ball having a fabric material outer surface)
22 preferably refers to a yellow fabric material.

23 References to "yellow" refer to any non-white fabric
24 material which is acceptable to the International
25 Tennis Federation (I.T.F.) (since yellow is an
26 accepted coloration of tennis ball according to the
27 I.T.F.). However, this is not exclusive, and other
28 coloured fabric materials (for example pink, green,
29 blue, etc) are also encompassed.

30

10019070.122001

1 The present invention will be now further described
2 with reference to the following, non-limiting example
3 and Figures in which:
4

5 **Figure 1** shows the reflectance curves of two prior
6 art felts in ball form (Nos 2 & 3) compared with the
7 Ultra High Visibility yellow felt (UHV F/Y) in fabric
8 form (No 1) of the invention.

9
10 **Figure 2** shows the reflectance curves of two other
11 felts (Nos 4 & 5) produced by the Applicant and
12 compared with the UHV F/Y felt (No 1) of the
13 invention, all in fabric form.

14
15 **Figure 3** shows the same data as Figure 2 but the data
16 used to produce the curves are generated by the
17 International Tennis Federation on their
18 spectrophotometer.

19
20 **Figure 4** shows the saturation (chroma) of the UHV F/Y
21 felt (No 1) of the invention compared with the four
22 prior art felts (Nos 2 to 5) used in Figures 1 to 3.

23
24 **Figure 5** shows the lightness of the same five felts
25 used in Figure 4.

26
27 **Figure 6** is an attempt to illustrate the position on
28 the colour circle by both chroma and hue of the five
29 samples used in the comparative data shown in Figures
30 1 to 5.

31

10019070-120001

1 **Example 1**

2 **Production of an ultra high visibility yellow felt**
3 **according to the method of the invention**

4
5 The felt used in this example is a fabric material
6 having an back surface made mainly in cotton and a
7 face side made of a wool and polyamide fibre felt
8 (the face side of the fabric forms the external face
9 of the ball). Only the face surface made of wool and
10 polyamide felt needs to be coloured. Wool and
11 polyamide are present in the weft in a ratio of about
12 60:40 with respect to the weight of wool and
13 polyamide fibres. The amount of cotton fibres in the
14 material represents about 15 % of the total weight of
15 the fabric material.

16
17 The felt is dyed using acid dyes in piece form using
18 a Softflow jet dyeing machine which is run at a
19 liquor ratio of between 6:1 and 8:1. The liquor is
20 the liquid in which the material is wetted before
21 the addition of the dyestuff. In most cases and in
22 particular in this example the liquor is water.

23
24 The dyeing method used in this example is as
25 follows:-

- 26 - The felt is entered into the machine cold and
27 the liquor ratio as indicated above;
28 - The pH is adjusted between 4.2 and 4.5 with
29 formic acid;
30 - The temperature is raised to 45°C and held for
31 3 minutes whilst checking pH;

- 1 - 0.5 grams per litre of BASOPAL NA (BASF) and
2 2% by weight of fibre of Lufibrol FW (BASF) are
3 added through the dosing system; and
4 - the machine is run for 5 minutes at 45°C.

5 The following dyeing method is then applied:

- 6 - 1.6% by weight of fibres of NYLOMINE
7 FLAVINE C-7G dyestuff is added through the
8 dosing system during a period of 2 minutes;
9 - the temperature is raised at a rate of
10 1.8°C per minute to 95°C and the machine is
11 run for 30 minutes at this temperature;
12 - the temperature is decreased to 40°C at a
13 rate of 2.5°C per minute; and
14 - the felt is rinsed twice with fresh water
15 and unloaded from the machine.

16

17 **Comparative data**

18

19 The colour characteristics of the felt dyed according
20 to the above described method are shown in Figures 1
21 to 6. Except for Figure 3, all data were measured by
22 the Applicant using CIE (Commission Internationale
23 d'Eclairage) CIELAB formula at a 10 degree
24 reflectance angle using standard D65 illuminant.

25

26 Figure 1 shows reflectance curves of an UHV yellow
27 felt (UHV F/Y) made according the method described in
28 Example 1 and of two competing felts in the form of
29 tennis balls produced respectively for the companies
30 Tretorn Sport and Penn Racquet Sports under the Trade
31 Names TRETORN TXT and PRO PENN. The felts used to

1 cover these balls are produced by Textech Industries.
2 We have found only minimal difference in the
3 spectrophotometric measurements made between a fabric
4 in sheet form and the same fabric when in the form of
5 completed tennis balls.

6
7 Figure 2 shows reflectance curves of the UHV F/Y felt
8 used in Figure 1 and of two other yellow felts, a
9 "standard" (Std.F/Y) one and an "high visibility" one
10 (Hi. Viz. F/Y), both produced by the company Milliken
11 (Woollen Speciality Products) under the respective
12 Trade Names PLAYNE'S 14 and PLAYNE'S 45. These felts
13 are used in the manufacture of tennis balls such as
14 the ones sold under the Trade Names DUNLOP FORT
15 (standard) and SLAZENGER WIMBLEDON (high visibility).

16
17 Figure 3 shows the same data as Figure 2 but the data
18 used to produce the curves are generated by the
19 International Tennis Federation (ITF) on their
20 spectrophotometer. This independent measurement shows
21 good correlation with the Applicant's own data.

22
23 Figures 4 and 5 show respectively the chroma and the
24 lightness of the five tested felts.

25
26 Figure 6 shows a graph displaying the combination of
27 both chroma and hue performances of the five tested
28 felts.

29
30 As can be seen from Figures 1 to 6, the colour of the
31 felt of this example of the invention demonstrates

10019070.12001

superior characteristics in all areas (i.e. chroma, hue lightness and reflectance). The performances, when compared to the closest prior art (i.e. the High Visibility felt manufactured by Milliken), are especially better for lightness and reflectance.

Figures 2 to 4 & 5 show that the high visibility felt has a higher level of saturation (chroma) but actually has a slight reduction in peak reflectance and in lightness when compared to the standard colour felt. This disadvantage does not exist with the colour of the UHV felt.

A summary table of the peak reflectance level, chroma, hue and lightness for the fabric according to the invention (UHV F/Y) and for the commercially available alternatives used above and a natural white tennis ball felt is given in Table 1 below.

Table 1

Product	Peak Reflectance Level	Chroma (Saturation)	Hue	Lightness
Natural White Tennis Ball Felt	78.46	8.9	92.4	87.8
Milliken Standard Yellow Felt (Std.F/Y)	122.4	98.2	108.8	96.5
Milliken High Visibility Yellow felt (Hi.Viz.F/Y)	119.8	112.0	101.3	94.2
UHV F/Y	129.9	113.4	104.7	97.9
Tretorn TXT Ball	113.1	100.9	104.5	93.6
Pro Penn Ball	124.4	95.8	108.1	95.7

1 Thus, the UHV F/Y felt of this invention can be used
2 for the manufacture of yellow tennis balls of
3 improved colour properties, which is obviously highly
4 desirable to tennis players. Such improved
5 properties permit, during a game, a more easy and
6 rapid catch (visualisation) of the incoming moving
7 ball by the tennis player and thus a quicker reaction
8 and positioning of the player with respect the ball.

9
10 The method and the product thus produced according to
11 the invention may be used for other purposes than
12 covering tennis balls. The high visibility of colour
13 material of the invention could also be used for
14 producing other items than tennis balls, especially
15 those where high visibility is important (for example
16 footballs - especially for indoor use - basketballs
17 and volleyballs).

18
19 Alternative dyeing technologies may be used, and
20 specific mention may be made of the following:

21
22 1. Winch beck

23
24 Winch beck dyeing is an alternative technology for
25 dyeing piece goods and pre-dates the Softflow jet-
26 dyeing apparatus. Whilst the dyeing method is
27 essentially the same as for jet-dyeing the liquor
28 ratio would be higher, normally 20:1 to 25:1.

29
30 In simple terms, this is a vertical stainless steel
31 tank; the top half of one side lifts up and down for

1 access and the top is vented. A large roller known
2 as a winch is contained within the top section.
3 There is a heating coil in the bottom section.
4
5 The tank is partially filled with water and the cloth
6 is then passed over the winch roller, through the
7 water and then back out of the machine. The two ends
8 of the cloth are sewn together to make an endless
9 rope. The winch is driven to continually rotate the
10 rope through the water.

11
12 Dyes and chemicals are pre-dissolved and then added
13 to the water. Steam is passed through the heating
14 coil to raise the bath temperature to 98°C. This
15 temperature is held for 30-45 minutes, after which
16 the tank is cooled by filling with cold water and
17 then draining. This is repeated until a safe
18 handling temperature is achieved after which the
19 cloth is removed.

20

21 Products used in the bath:

22

23 Fluorescent yellow dyestuff - colouring material.

24 Glauber salts - acts as a levelling agent.

25 Formic acid - to lower the pH making the cloth more
26 attractive to dyestuff.

27

28 2. Loose stock machine

29

30 This is a circular stainless steel tank (or vat),
31 from 1 metre to 3 metres diameter, which is partially

10019070.122001

1 filled with water. The material, in the form of
2 loose wool and/or nylon fibres, which have been pre-
3 washed is loaded into a cage. This cage then has a
4 lid attached and is placed inside the outer tank.
5 Dyestuff and chemicals are pre-dissolved inside a
6 header tank and then pumped into the tank and through
7 the stock in the cage.

8
9 The temperature of the vat is raised to 98°C and held
10 for 30-45 minutes. The dye liquor is drained and
11 fresh cold water pumped through to rinse and cool the
12 loose stock.

13
14 The products used are the same as for winch dyeing.

15
16 After dyeing the fibres are processed into fabric
17 form.

18
19 3. Package dyeing

20
21 Yarn is wound onto a stainless-steel cylinder which
22 is perforated, allowing the dyeing liquor to be
23 pumped through the yarn package from inside to out
24 and vice versa. The yarn package is loaded into a
25 circular, stainless steel tank and then pre-dissolved
26 dyes and chemicals are pumped in.

27
28 The temperature of the liquor is raised to 98°C by a
29 steam heating coil. This temperature is maintained
30 for approximately 1 hour. The packages are then
31 rinsed with cool water to cool the bath and remove

10019070.122001

- 1 residual dyestuff. The batch is left to drain and
- 2 then removed from the vessel.
- 3
- 4 Products used are the same as for winch dyeing.

10019070-122001

Claims :

1. A method of dyeing a fabric material, said material being a woven felt which comprises warp and weft yarns, said method comprising the step of contacting said woven felt with a bleaching agent prior to or simultaneously with a fluorescent dye providing said colour.
2. The method as claimed in Claim 1, wherein the dyestuff is a yellow dye.
3. The method as claimed in either Claim 1 or 2, wherein said yellow dye has a colour index number acid yellow 250.
4. The method as claimed in any one of Claims 1 to 3, wherein said material is made from a mixture of fibres of different types.
5. The method as claimed in any one of Claims 1 to 4, wherein said material comprises a mixture of wool and synthetic fibres.
6. The method as claimed in Claim 5, wherein said synthetic fibres are polyamide fibres.
7. The method as claimed in Claim 6, wherein said polyamide fibres are Nylon 6,6 fibres.

- 1 8. The method as claimed in any one of Claims 1 to
2 7, wherein the content of wool fibres in said
3 material is at least 20% by weight.
4
5 9. The method as claimed in any one of Claims 1 to
6 8, wherein the content of wool fibres in said
7 material is at least 25% by weight.
8
9 10. The method as claimed in any one of Claims 1 to
10 9, wherein the content of wool fibres in said
11 material is at least 40% by weight.
12
13 11. The method as claimed in any one of Claims 1 to
14 10, wherein said weft yarns comprise at least
15 20% by weight of wool.
16
17 12. The method as claimed in any one of Claims 1 to
18 10, wherein said weft yarns comprise at least
19 30% by weight of wool.
20
21 13. The method as claimed in any one of Claims 1 to
22 10, wherein said weft yarns comprise at least
23 40% by weight of wool.
24
25 14. The method as claimed in any one of Claims 1 to
26 13, wherein said material is processed in piece
27 form.
28
29 15. The method as claimed in any one of Claims 1 to
30 14, wherein said material is contacted with a
31 partitioning agent.

- 1 16. The method as claimed in Claim 15, wherein said
2 partitioning agent is an alkylarylsulphonate in
3 water and comprises 50-60% by weight of the
4 salt of dodecylbenzenesulphonic and
5 triethanolamine.
6
- 7 17. The method as claimed in any one of Claims 1 to
8 16, wherein said material is treated using a
9 jet-dyeing apparatus.
10
- 11 18. The method as claimed in Claim 17, wherein a
12 liquor ratio of from 6:1 to 8:1 is used to run
13 said jet-dyeing apparatus.
14
- 15 19. The method as claimed in Claim 15, wherein the
16 pH of the liquor is of from 4.2 to 4.5.
17
- 18 20. The method as claimed in any one of Claims 1 to
19 19, wherein said material is contacted with the
20 bleaching agent prior to said material being
21 contacted with said fluorescent dye.
22
- 23 21. The method as claimed in any one of Claims 15
24 to 16, wherein said material is contacted with
25 the partitioning agent prior to said material
26 being contacted with said fluorescent dye.
27
- 28 22. The method as claimed in any one of Claims 15,
29 16 and 18, wherein said bleaching agent is
30 added simultaneously or quasi-simultaneously
31 with the partitioning agent.
32

- 1 23. The method as claimed in any one of Claims 1 to
2 22, wherein said bleaching agent is an
3 inorganic reducing agent with chelating agents
4 and comprises 30-40% by weight tetrasodium
5 ethylene-diaminetetraacetate and 30-40% by
6 weight disodium disulphite.
7
- 8 24. A coloured fabric material obtainable according
9 to the method described in any one of Claims 1
10 to 23.
11
- 12 25. The use of a dyed fabric material as claimed in
13 Claim 24 for the manufacture of a sports ball.
14
- 15 26. The use claimed in Claim 25, wherein said
16 sports ball is a tennis ball.
17
- 18 27. A coloured (non-white) fabric material suitable
19 for use in sports ball manufacture, said
20 material being a woven felt which comprises
21 warp and weft yarns, wherein said material
22 includes wool fibres and exhibits the following
23 characteristics:
24 i) a chroma value of 100 or more;
25 ii) a lightness value of 95 or more; and
26 iii) a reflectance value of 120 or more.
27
- 28 28. The fabric material of Claim 27, wherein said
29 chroma value is 105 or more.
30

- 1 29. The fabric material as claimed in either one of
2 Claims 27 and 28, wherein said lightness value
3 is 96 or more.
4
- 5 30. The fabric material as claimed in any one of
6 Claims 27 to 29, wherein said reflectance value
7 is 125 or more.
8
- 9 31. The fabric material as claimed in any one of
10 Claims 27 to 29, which exhibits the following
11 characteristics:
12 i) a chroma value of 110 or more;
13 ii) a lightness value of 97 or more; and
14 iii) a reflectance value of 128 or more.
15
- 16 32. A white fabric material suitable for use in
17 sports ball manufacture, said material being a
18 woven felt which comprises warp and weft yarns,
19 wherein said material includes wool fibres and
20 exhibits the following characteristics:
21 i) a chroma value of 14 or less;
22 ii) a lightness value of 85 or more;
23 and
24 iii) a reflectance value of 100 or
25 more.
26
- 27 33. A white fabric material as claimed in Claim 32,
28 wherein said chroma value is 8 or lower.
29
- 30 34. A white fabric material as claimed in either
31 one of Claims 32 and 33, having a lightness
32 value of 92 or greater.

10019070.122001

- 1
2 35. A white fabric material as claimed in any one
3 of Claims 32 to 34, having a reflectance value
4 of 85 or more.
5
6 36. A white fabric material as claimed in any one
7 of Claims 32 to 35, which exhibits the
8 following characteristics:
9 i) a chroma value of 5 or less;
10 ii) a lightness value of 93 or more; and
11 iii) a reflectance value of 90 or more.
12
13 37. A fabric material as claimed in any one of
14 Claims 27 to 36, wherein said material is made
15 of a mixture of fibres of different types.
16
17 38. A fabric material as claimed in any one of
18 Claims 27 to 37, wherein said material
19 comprises a mixture of wool and synthetic
20 fibres.
21
22 39. A fabric material as claimed in Claim 38,
23 wherein said synthetic fibres are polyamide
24 fibres.
25
26 40. A fabric material as claimed in Claim 39,
27 wherein said polyamide fibres are Nylon 6,6
28 fibres.
29
30 41. A fabric material as claimed in any one of
31 Claims 27 to 44, wherein the content of wool

1 fibres in said material is at least 20% by
2 weight.

3
4 42. A fabric material as claimed in any one of
5 Claims 27 to 41, wherein the content of wool
6 fibres in said material is at least 40% by
7 weight.

8
9 43. A fabric material as claimed in any one of
10 Claims 27 to 42, wherein said weft yarns
11 comprise at least 20% by weight of wool.

12
13 44. A fabric material as claimed in any one of
14 Claims 27 to 43, wherein said weft yarns
15 comprise at least 30% by weight of wool.

16
17 45. A fabric material as claimed in any one of
18 Claims 27 to 44, wherein said weft yarns
19 comprise at least 40% by weight of wool.

20
21 46. A sports ball having a fabric material outer
22 surface, said fabric material being a fabric
23 material as defined in any one of Claims 27 to
24 45.

25
26 47. A sports ball as claimed in Claim 46 which is a
27 tennis ball.


28
29 48. A sports ball having a fabric material outer
30 surface, said fabric material being a fabric
31 material as obtained by the method of any one
32 of Claims 1 to 24.

- 1
2 49. A sports ball as claimed in Claim 48 which is a
3 tennis ball.

100221.07061001

1 / 6

UHV FY	
1.	—
Trelorn TXT	
2.	- - -
Pro Penn	
3.





Wavelength (NM)

Fig. 1

100221-02061001

2 / 6



Wavelength (NM)

Fig. 2

100221-02061001

WO 00/79038

10/019070
PCT/GB00/02290

3 / 6




Fig. 3

4/6




Fig. 4

5/6




Fig. 5

6 / 6


Comparison of tennis ball felts
(Chroma & Hue)

Fig. 6

United States Patent Application
COMBINED DECLARATION AND POWER OF ATTORNEY

Attorney's Docket Number MUR-858215

As a below named inventors I hereby declare that:
My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor of the subject matter which is claimed and for which a patent is sought on the invention entitled:

"Dyed Fabric Material, Method of Producing the Same and Use
of the Fabric Material in the Manufacture of Sports Balls"

the specification of which:

[c] was filed as a PCT International Application Number PCT/GB00/02290 on 23 June 2000.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith:

Paul F Prestia	Reg No <u>23,031</u>	Christopher R Lewis	Reg No <u>36,201</u>
Allan Ratner	Reg No <u>19,717</u>	Louis W Beardell Jr	Reg No <u>40,506</u>
Andrew L Ney	Reg No <u>20,300</u>	Rocco L Adomato	Reg No <u>40,480</u>
Kenneth N Nigon	Reg No <u>31,549</u>	Jacques L Etkowicz	Reg No <u>41,738</u>
Kevin R Casey	Reg No <u>32,117</u>	Eric A Dichter	Reg No <u>41,708</u>
Benjamin E Leace	Reg No <u>33,412</u>	Mark J Marcelli	Reg No <u>38,593</u>
James C Simmons	Reg No <u>24,842</u>	Joshua L Cohen	Reg No <u>38,040</u>
Lawrence E Ashery	Reg No <u>34,515</u>	Christopher J Dervishian	Reg No <u>42,480</u>
Robert L Anderson	Reg No <u>25,771</u>	Jack J Jankovitz	Reg No <u>42,690</u>

Send correspondence to:

RATNER & PRESTIA
Suite 301, One Westlakes,
Berwyn, P O Box 980,
Valley Forge, PA 19482-0980

Telephone calls: Allan Ratner (610) 407 0700

I acknowledge the duty to disclose information which is material to the examination of this Application in accordance with Title 37, Code of Federal Regulations, Section 1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119 of any foreign Application(s) for Patent or inventor's certificate or of any PCT International Application(s) designating at least one country other than the United States of America listed below, and have also identified below any foreign Applications for Patent or inventor's certificate or any PCT International Application(s) designating at least one country other than the United States of America filed by me on the same subject matter and having a filing date before that of the Application(s) of which priority is claimed:

COUNTRY	APPLICATION NUMBER	DATE OF FILING	PRIORITY CLAIMED
United Kingdom	9914510.4	23 June 1999	Yes
United Kingdom	0009783.2	20 April 2000	Yes
United Kingdom	0011752.3	17 May 2000	Yes

FIRST INVENTOR

Full Name : BRASIER, Alan John
Residence: Gloucestershire, United Kingdom GBX
Citizenship: British (Great Britain)
Post Office Address: 53 Swallowcroft, Eastington, Stonehouse, Gloucestershire, GL10 3BH,
United Kingdom

SECOND INVENTOR

Full Name: SMITH, David Anthony
Residence: Gloucestershire, United Kingdom GBX
Citizenship: British (Great Britain)
Post Office Address: Mayflower Lodge, Colethorp, Haresfield, Nr Stonehouse, Gloucestershire,
GL10 3EJ, United Kingdom

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on the information and belief are believed to be true; and further that these statements were made with the knowledge that wilful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such wilful false statements may jeopardize the validity of the Application or any Patent issuing thereon.

Signature of First Inventor [Signature] Date 13 December 2001

Signature of Second Inventor [Signature] Date 13 Dec 2001